

# OUTLANDER™ 800 H.O. EFI

|  | SPECIFICATIONS | OUTLANDER 800 H.O. EFI 4x4   | OUTLANDER MAX 800 H.O. EFI 4x4  |  |
|--|----------------|------------------------------|---|--|
|  <p><b>Outlander 800 H.O. EFI 4x4</b></p>          | ENGINE         | Type                         | 799.9cc, 4-stroke, V-twin, liquid-cooled, 8-valve SOHC  | 799.9cc, 4-stroke, V-twin, liquid-cooled, 8-valve SOHC   |
|  |                | Bore & Stroke                | 91 x 62 mm  | 91 x 62 mm   |
|  <p><b>Outlander 800 H.O. EFI XT 4x4</b></p>      | CHASSIS        | Torque                       | 73 Nm @ 5,500 RPM   | 73 Nm @ 5,500 RPM  |
|  |                | Fuel Delivery                | 46 mm Throttle Body, 2 Siemens <sup>†</sup> VDO injectors   | 46 mm Throttle Body, 2 Siemens VDO injectors   |
|  |                | Starting System              | Electric  | Electric   |
|  |                | Transmission                 | CVT, sub-transmission with high, low, park, neutral & reverse   | CVT, sub-transmission with high, low, park, neutral & reverse  |
|  |                | Drive Train                  | Selectable 2w/4w shaft driven with Visco-Lok <sup>†</sup> front differential  | Selectable 2w/4w shaft driven with Visco-Lok front differential  |
|  |                | Frame                        | SST   | SST  |
|  |                | Front Suspension Type        | Double A-arm, forged aluminum upper arm   | Double A-arm, forged aluminum upper arm  |
|  |                | Travel                       | 8 in (203 mm)   | 8 in (203 mm)  |
|  <p><b>Outlander MAX 800 H.O. EFI 4x4</b></p>    | DIMENSIONS     | Rear Suspension Type         | TTL independent   | TTL independent  |
|  |                | Travel                       | 9 in (228.6 mm)   | 9 in (228.6 mm)  |
|  |                | Front Brake                  | 2 inboard hydraulic discs   | 2 inboard hydraulic discs  |
|  |                | Rear Brake                   | 1 inboard hydraulic disc  | 1 inboard hydraulic disc   |
|  |                | Tires/Front                  | 26 x 8 x 12 in<br>660.4 x 203 x 305 mm  | 26 x 8 x 12 in<br>660.4 x 203 x 305 mm   |
|  |                | Tires/Rear                   | 26 x 10 x 12 in<br>660.4 x 254 x 305 mm   | 26 x 10 x 12 in<br>660.4 x 254 x 305 mm  |
|  |                | Wheels                       | Steel   | Steel  |
|  |                | L x W x H (in)               | 86 x 46 x 45 in   | 94 x 46 x 45 in  |
|  |                | L x W x H (mm)               | 2,184 x 1,168 x 1,143 mm  | 2,387 x 1,168 x 1,143 mm   |
|  |                | Wheelbase                    | 51 in (1,295 mm)  | 59 in (1,499 mm)   |
|  <p><b>Outlander MAX 800 H.O. EFI XT 4x4</b></p> | FEATURES       | Seat Height                  | 34.5 in (877 mm)  | 34.5 in (877 mm)   |
|  |                | Dry Weight                   | 657 lbs (298 kg)  | 707 lbs (321 kg)   |
|  |                | Ground Clearance             | 12 in (305 mm)  | 12 in (305 mm)   |
|  |                | Rack Capacity                | Front: 100 lbs (45 kg)<br>Rear: 200 lbs (90 kg)   | Front: 100 lbs (45 kg)<br>Rear: 200 lbs (90 kg)  |
|  |                | Towing Capacity              | 1,300 lbs (590 kg)  | 1,300 lbs (590 kg)   |
|  |                | Fuel Capacity                | 5.3 US gal (20 L)   | 5.3 US gal (20 L)  |
|  |                | Instrumentation              | Multi-function digital LCD gauge: Speedometer, tachometer, odometer, trip & hour meter, fuel, gear position & 4x4 indicator, diagnostics, auto shut off after 15 minutes                        | Multi-function digital LCD gauge: Speedometer, tachometer, odometer, trip & hour meter, fuel, gear position & 4x4 indicator, diagnostics, auto shut off after 15 minutes           |
|  |                | Anti-Theft                   | D.E.S.S. (Digital Encoded Security System)  | D.E.S.S. (Digital Encoded Security System)   |
|  |                | Storage                      | Rear storage 5.3 US gal (20 L)  | Rear storage 5.3 US gal (20 L)<br>CRS (Convertible Rack System)  |
|  |                | Electrical Lighting          | Prewired for winch<br>2 fender mounted headlamps (35W) with tail light/brake light  | Prewired for winch<br>2 fender mounted headlamps (35W) with tail light/brake light   |
|  <p><b>Outlander MAX 800 H.O. EFI XT 4x4</b></p> | PACKAGE        | DC Outlet                    | Lighter type in console, standard connector in the back (15A)   | Lighter type in console, standard connector in the back (15A)  |
|  |                | Standard Colors              | Yellow, Viper Red   | Yellow, Viper Red  |
|  <p><b>Outlander MAX 800 H.O. EFI XT 4x4</b></p> | PACKAGE        | XT Package Content Available | BRP XL3000 winch, roller fairlead, wired remote control, cast aluminum rims, aggressive tread Carlisle <sup>†</sup> ACT radial tires, heavy-duty front & rear bumpers, handlebar wind deflector | BRP XL3000 winch, roller fairlead, wired remote control, cast aluminum rims, aggressive tread Carlisle ACT radial tires, heavy-duty front & rear bumpers, handlebar wind deflector |
|  |                | XT Colors                    | Yellow, Viper Red, Laurentian Green, Camo   | Yellow, Viper Red, Laurentian Green, Camo  |

©2007 Bombardier Recreational Products Inc. (BRP). All rights reserved.™ and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S. call the ATV Safety Institute at 1(800) 887-2887. In Canada, call the Canadian Safety Council at 1(613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Can-Am™ Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.

**can-am**  
THE ULTIMATE RIDE™

